

We keep on stock for you:

Tor spherical heads DIN 28011 from plate to P265GH, M.T.C. 3.1B, VA-bevel

| ∅ / thickn. | 4 | 5 | 6 | 8 | 10 | 12 |
|-------------|---|---|---|---|----|----|
| 33,0 | X | | | | | |
| 42,0 | X | | | | | |
| 60,3 | X | X | | | | |
| 76,1 | X | | | | | |
| 88,9 | X | | X | | | |
| 114,3 | X | | X | | | |
| 139,7 | X | | X | X | | |
| 159,0 | X | | X | | | |
| 168,3 | X | X | X | X | | |
| 193,7 | X | X | | X | | |
| 219,1 | | X | X | X | X | X |
| 244,5 | | X | X | | | |
| 273,0 | | X | X | X | X | X |
| 300,0 | X | X | X | X | | |
| 323,9 | | X | X | X | X | X |
| 350,0 | X | | X | | | |
| 355,6 | | X | X | X | X | X |
| 368,0 | | X | | | | |
| 400,0 | X | X | X | X | | |
| 406,4 | X | | X | X | X | X |
| 419,0 | | X | | X | X | |
| 450,0 | | X | X | X | | X |
| 457,2 | | | X | X | | X |
| 500,0 | | X | X | X | | X |
| 508,0 | | X | X | X | X | |
| 550,0 | | X | X | | X | |
| 600,0 | X | X | X | X | X | X |
| 609,6 | X | | X | X | | X |
| 650,0 | | X | X | X | X | |
| 700,0 | | X | X | X | | X |
| 711,2 | | | X | X | X | X |
| 750,0 | | X | X | X | | X |
| 800,0 | X | X | X | X | X | X |
| 812,8 | | | X | X | X | |
| 850,0 | | | X | | X | X |
| 900,0 | | X | X | X | X | X |
| 914,4 | | | X | | X | |
| 950,0 | | | | X | X | |
| 1000,0 | | X | X | X | X | X |
| 1016,0 | | | | | X | |
| 1100,0 | | | X | X | X | X |
| 1150,0 | | | | X | X | |
| 1200,0 | | | X | X | X | X |
| 1250,0 | | | X | | X | X |
| 1300,0 | | | | X | X | X |
| 1400,0 | | | X | X | X | X |
| 1500,0 | | | X | X | X | X |
| 1600,0 | | | X | X | X | X |
| 1800,0 | | | | X | X | X |
| 2000,0 | | | | X | X | X |
| ∅ / thickn. | 4 | 5 | 6 | 8 | 10 | 12 |